

Express Mail No.  
EV 311435868 US

PATENT

**MEDIA ACQUISITION, PROCESSING AND DISTRIBUTION SYSTEM  
FOR THE INTERNET**

5 The present application is related by subject matter to U.S. Application  
Serial No. 09/357,836 (Atty. Dkt. No. 032374-003) entitled Web-Based Media  
Submission Tool, filed on July 21, 1999 and incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

10 **1. Field of the Invention**

The present invention relates to the acquisition, processing and distribution of  
media objects on the Internet and, more particularly, to such systems for use in  
applications wherein there are multiple originators of media objects that will be  
viewed in multiple web sites having different viewing requirements.

15 **2. State of the Art**

Much of the phenomenal success of the Web is attributable to its graphical  
nature. Literally, a picture is worth a thousand words. The capture of digital images  
has become routine, using digital cameras (still and video) and scanners.  
Nevertheless, although the handling of images by Web site creators has achieved a

high degree of automation, for the average user manipulating and sharing digital images over the Internet remains a cumbersome and daunting process. Piecemeal solutions that have been devised for handling digital images require a level of sophistication that is beyond that of the ordinary user. Additionally, where automated solutions do not exist, time consuming and error-prone human and manual intervention are required to manipulate or share images. Such manual intervention for transferring a digital image may include, for example, first downloading a FTP program, then installing it, then running it and connecting it to an FTP server by typing the server name in the connection dialog, then navigating to the proper subdirectory, selecting the files to be uploaded, making sure that the program is in binary transfer mode, then sending the files. For the average user, such an involved process is a disadvantage.

Additionally, as technologies advance and casual users begin to experiment with other image types, such as streaming video, 3D objects, slide shows, movies, and accompanying sound files, the processes required to share these rich media types on the Internet becomes exponentially more complicated and prohibitive. As the realization of the Internet as an interactive, content rich medium becomes more and more a reality, the need for enabling the acquisition and distribution of rich content and media on the Internet will become the gating factor to its long-term success.

Once specific application of handling media over the Internet is in the real-estate market. It has been reported that over 25% of prospective residential home-buyers use the Internet as a means for locating properties of potential interest. There are many web sites dedicated to this purpose, including major real estate portals (e.g., Realtor.com and HomeAdvisor), national and regional brokerages, and individual realtor or broker web sites, to name a few. To be effective, these sites must provide rich visual content in the form of images of the properties listed. The image content can take the form of a single still image, multiple still images, slide shows comprised of a sequence of still images, immersive images (360 degree

views), and video tours. These images can also have audio associated with them. The term Amedia object® is used generically herein to refer to all types of such images, including audio and graphic objects.

5 While anyone can access the Internet through a browser, getting images posted to the Internet is a complicated process generally requiring a high degree of technical proficiency and specialized software tools. It is even more difficult when the media objects are of multiple types (still images, immersive images, video, etc.) and are created by different originators. For example, a real estate listing might  
10 include an image captured by a multiple listing service photographer, an immersive image captured by a professional photographer, and multiple still images taken by the real estate agent herself. Add to this the fact that all of these media objects need to be displayed on multiple web sites that will have different viewing requirements. For example, a national real estate portal may only accept still images of a certain  
15 size and quality, say 300 x 200 pixels at a jpeg compression setting of 60%, while an agent's individual web site may require a 390 x 260 pixel representation of the images at a different quality setting. Additionally, different browser versions have different viewing requirements for certain media object types. It is apparent that the problems associated with acquiring media objects from multiple sources and  
20 distributing them in the required form to multiple destination web sites are complex.

There are web sites today that offer a subset of this functionality specifically in the on line photo sharing market. These sites allow users to store their personal photographs, display them in a thumbnail or larger view and invite family and  
25 friends to view the pictures. These photo sharing sites let users upload digital pictures directly or have film processed and then posted to the web site. The purpose of these sites is to accommodate image uploads from many users within a proprietary system and where the image destination is intended to stay within that system.

30 The present invention teaches a Media Acquisition, Processing and

Distribution (MAPD) system that solves many of the problems of handling media over the internet such as encountered in the real-estate market and photo sharing market. The Media Acquisition, Processing and Distribution (MAPD) system of the present invention has three major components: (1) media acquisition, (2) media  
5 processing and (3) media distribution (via hosting or mirroring). The purpose of the MAPD system is to enable multiple users without computer expertise to easily submit media objects that, after appropriate processing in accordance with pre-defined requirements, are viewable on multiple web sites.

10 The MAPD system of the present invention specifically handles image upload within an open system and that system is designed to process and distribute media objects outside of itself, to be viewed in multiple web sites having different viewing requirements such as desired in the real-estate market. Additionally, the system of the present invention is designed such that the proprietary systems used in  
15 the photo sharing sites are unique to each web site and are not designed to be deployed across several web sites, markets or partners. Finally, the MAPD system of the present invention is designed to be used by varying and different web sites across many markets and partners. One important aspect of the MAPD system is its API or abstraction layer that specifically allows multiple web sites to integrate the MAPD  
20 system functionality.

#### SUMMARY OF THE INVENTION

The present invention, generally speaking, provides a broad-based solution for the acquisition, processing and automatic distribution of media objects via the  
25 Internet in a manner that does not require a high degree of technical proficiency. Specifically, the present invention provides a media acquisition, processing and distribution system for media objects submitted by multiple users for viewing within a plurality of destination web sites that have different media object viewing requirements. The invention provides means for each of the originators to associate  
30 one or more local media objects with a media object interface within a browser. Means are provided for storing information that defines the media object viewing

requirements for each of the destination web sites. A remote server or servers receives the media objects from each originator and, based on the information stored in the database, processes the media objects in accordance with the media object viewing requirements of the destination web sites. In a hosting configuration, the remote server(s) send a URL to each destination web site that links the site back to the processed media object for viewing. In a mirroring configuration, the remote server(s) distribute the processed media objects to the destination web site servers.

In accordance with a further aspect of the present invention, within the MAPD client/server architecture, means are provided for intelligently processing the media objects both on the client and server, thereby enabling a more efficient use of bandwidth.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention may be further understood from the following description in conjunction with the appended drawings. In the drawing:

**Fig. 1** is a diagram illustrating information flow in accordance with one aspect of the invention;

**Fig. 2** is a more detailed block diagram corresponding to the diagram of Figure 1;

**Fig. 3** is a diagram illustrating information flow in accordance with another aspect of the invention;

**Fig. 4** is a more detailed block diagram corresponding to the diagram of Figure 3;

**Fig. 5** is a diagram of an exemplary Web page providing image acquisition functions;

**Fig. 6** is a conceptual block diagram of the MAPD system network imaging system work flow and media processing engine scalability;

**Fig. 7** is a system block diagram of the hardware partition for MAPD system network imaging system mirroring service;

**Fig. 8** is a diagram showing the relationship of certain areas of the mirroring service;

**Fig. 9** is a diagram illustrating three-tier partitioning of the network imaging

system;

**Fig. 10** is an entity/relationship diagram of the database of Figure 9;

**Fig. 11** is a diagram illustrating relationships between account, service and storage entities;

5 **Fig. 12** is a diagram illustrating relationships between mirror service entities; and

**Fig. 13** is a method called when a new media object arrives at a client site.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 The following description describes a system for MAPD that enables the acquisition, processing and distribution of media objects from multiple users to multiple viewing web sites on the Internet. The term Amedia object@ as used herein refers broadly to any form of digital image or graphical file, including still images, PDF files, video images, audio, slide shows, etc. Although in the following description the submission and processing of still images is described in greatest  
15 detail, the same principles apply equally to media objects of all descriptions and apply equally to groups of multiple images.

The MAPD system of the present invention is for use in those applications wherein multiple users of the system have a need to submit media objects for  
20 viewing on multiple destination web sites that, in general, have different viewing requirements. The term Aviewing requirements@ refers broadly to the various and unique ways media objects are displayed by web sites. Each web site places different technical requirements and constraints on the way that site uniquely displays media objects and therefore allows for viewing of media objects by visitors to the site. In  
25 accordance with the present invention, means are provided in the form of a Aprepare and post@ tool for each of the originators of media objects to associate one or more media objects with a media object identifier on a locally viewable web page, and for uploading the media object or objects to at least one remote server. A database stores information that defines the media object viewing requirements for each of the  
30 destination web sites. Within the MAPD client/server architecture, either on the client or server, the MAPD system processes the input media objects to meet the

viewing requirements that are specified for each of the destination web sites. Such processing may take the form of image resizing, reformatting (changing the file format) , encoding in the case of video, specifying media object storage location and browser version support just to name a few. The MAPD system then either delivers a media object URL to the destination web sites (hosting service) or transfers the processed media objects to the destination web sites ready for viewing (mirroring service). Specifically, the hosting service delivers a media object URL to a web page, allowing the media object to be requested by a customer web site and served by the MAPD system. The mirroring service delivers the actual media object, or other related data such as a media object URL, to a remote database to be served by the host of the destination web site.

Using MAPD system, end users can submit media objects in an immediate and intuitive manner. No technical sophistication is required. In particular, understanding technical terms such as JPEG, resolution, pixel, kilobyte, transfer protocol, IP address, etc., is not required, since the MAPD system automatically and transparently handles all of these tasks for the end user.

For on-line commerce customers dealing with high transaction load web sites, hosting is appealing. The MAPD system hosting service allows these customers to incorporate rich media (where rich media can be generally defined as combinations of different media objects such as pictures, movies, sound clips, etc.) into interactive web sites. The MAPD system hosting service provides this rich media to web sites without requiring that they bear the overhead costs associated with hosting the media objects on their own servers or without the technical expertise required to process and create rich media. Referring to Figure 1, the MAPD system hosting service entails the following step-by-step process:

1. A media object is submitted by an end user (originator) dragging content into a MAPD system customer's web page. Media object ID data is also collected.

2. The media object may be pre-processed, such as converted, reduced, enhanced, etc., on the client within the MAPD client/server architecture.

3. The media object is uploaded into the MAPD system with ID information.

4. The media object is processed by the MAPD system in accordance with a profile that represents the requirements of the destination web sites. The requirement data is stored in a database and the media object is stored on a file server.

5. The MAPD system transparently returns a URL (representing the media object location) to the customer's web page. The media object source URL is embedded in the HTML in the customer's web page and returned to the customer's web server.

6. A hit by an end user (requestor) to the MAPD system customer's web page where the media object source URL is embedded causes the customer's server to request insertion of the media object hosted from the MAPD system.

7. The requested media object is served by the MAPD system and integrated into the customer's web page in real time as the web page draws.

8. The end user's (requestor's) browser presents the finished web page to the end user.

Transaction flow for the host service may be further appreciated with reference to Figure 2. Transaction flow begins with a MAPD system customer's web page having embedded in it the Aprepare and post@ tool. The Aprepare and post@ tool is represented on the web page as a media object identifier into which the user drags and drops a selected media object. The media object identifier may take the form of a Java applet, an ActiveX control, etc. The function of the identifier is to



receive a media object, display a thumbnail or visual representation of the media object, and (optionally) perform preprocessing of the media object. A separate component may be used to upload the media object in response to the user clicking on a Send button. In an exemplary embodiment, clicking on the Send button  
5 activates a COM component of the Aprepare and post@ tool, called the Media Sender, for uploading the media object to the MAPD system (step 1).

The MAPD system includes processing capabilities in the form of a "media processing engine" and media object storage including a database and a file system  
10 (e.g., file server). When media objects are received, they are "logged" into the database, processed if required, and stored in the file system. As shown in step 2, a media object source URL (IMG SRC URL) is returned to the end user (originator) machine that was used to view the customer's web page. The IMG SRC URL is in turn sent with accompanying form data to the destination web site (step 3).

At the destination web site, a web page is created having HTML that contains the IMG SRC reference. For example, the web page may describe a real estate listing and the media object may be an image of the property being listed. When an end user requests to view the web page (a hit to the web page occurs), HTML  
20 containing the IMG SRC URL is delivered to the end user's (requestor=s) computer from the destination web site. The media object itself is delivered separately from the MAPD system but at the same time the destination web page is served (step 5).

Some customers may prefer to host media objects on their own servers. In  
25 this instance, a MAPD system mirroring service is used. Referring to Figure 3, the media object mirroring service entails the following steps:

1. A media object is submitted by an end user (originator) dragging content into a MAPD system customer's web page. Media object ID data is also collected.  
30

2. The media object may be pre-processed, such as converted, reduced,

enhanced, etc.

3. The media object is uploaded to the MAPD system with ID information.

5 4. The media object and data are received by the MAPD system and the data is stored in a database while the media object is stored on a file server.

10 5. A request is placed in the distribution queue notifying the servers that additional processing and preparation may then be required prior to sending.

6. The media object is processed in accordance with a profile that represents the viewing requirements of the destination web sites and the processed media object is distributed to the customer's web server (second location) or to other web servers (e.g., customer affiliate locations) approved by the customer.

15 7. The media object and ID information are received by the second location and are processed by the customer's servers so that the ID information is automatically stored in a database and the media object is stored in accordance with pre-determined instructions per the second location.

20 8. When an end user (requestor) hits the customer's web sites that contain media objects from the MAPD system, the web sites and media objects are served from the customer's web server.

25 Transaction flow for the mirror service may be further appreciated with reference to Figure 4. As in the case of the hosting service, transaction flow for the mirroring service begins with a MAPD system customer web page having embedded in it the Aprepare and post@ tool, represented as a media object identifier. The end user drops a selected media object into the media object identifier and clicks on the  
30 Send button, sending the media object to the MAPD system central server (step 1). A return code is returned (step 2) to the COM component indicating whether or not

submission has been successful.

On central servers within MAPD system, the media object is processed in accordance with a stored customer profile. The media object is then sent directly (step 3) to the customer's web site servers, where it is stored. A return code is returned (step 4) to the MAPD system indicating success or failure of media object transfer to the destination web sites.

As in the case of the hosting service, at each destination web site, a web page is created having HTML containing the IMG SRC reference. However in most mirroring scenarios, different from the hosting service, when an end user (requestor) hit to the web page occurs, the web page and the media object are delivered directly from the customer's servers (steps 5 and 6).

Another implementation of mirroring may not send the media object itself to the MAPD system customer or customer affiliate locations. Other data that references the media object, such as the IMG SRC URL, may be distributed directly to the customer's servers and automatically integrated with web page data. The URL in hosting is returned immediately to the web page where the submission originates. The URL in mirroring is forwarded to another server (second location) not related to the web page where the submission originates. In this instance, the media object will be served from the MAPD system.

Referring to the real estate industry example stated earlier, Figure 5, is an example of a realty web page featuring the described Aprepare and post@ functionality of the MAPD system. The end user (originator) drags and drops photos into media object identifiers and selects appropriate captions for the media object, e.g., living room, family room, etc. The captions may be typed in or selected from menus. The end user also supplies identifying information, in this instance the multiple listing service number. When the end user clicks the Send Photos button, the media objects are processed and transported immediately according to the.

configuration of the tool and in accordance with the hosting service or the mirroring service previously described.

There are three ways media objects become associated with a media object identifier. The first is through a "drag and drop" behavior where the user clicks on a media object to select the one they want to submit. The media object is then dragged to the media object identifier. Releasing the mouse button associates the media object with the media object identifier. This behavior is allowed in web browsers that support drag and drop functionality. The Aprepare and post@ tools enable these browsers to accept media objects via drag and drop by providing the media object identifier as an ActiveX component.

The second way to associate a media with the media object identifier is to click on the media object identifier to browse for media objects, then select the media object of choice. This method is made available for web browsers where the media object identifier needs to be a pure Java component. (Such as "signed applet browsers" like Netscape Navigator). In this instance, the user may be asked to choose a media object in a similar manner as when choosing a file to be opened, either by graphical navigation or by specifying a path name. For example, a prompt associated with the media object identifier may be displayed prompting the user to click within the media object identifier. Clicking within the media object identifier brings up a browse dialog. Using the browse dialog, the user selects the desired media object, which is then placed in the media object identifier. The Aprepare and post@ tools will generate a visual representation or thumbnail of the media object, a feature currently not available in signed applet browsers.

A variation of the second way to associate a media object with the media object identifier involves support for older browser versions, also referred to as minimal browsers. Browsers in this category include versions 2.X and 3.X. Also considered part of the minimal browser category are all browsers used on the Macintosh platform. To accommodate complex file sending requirements from

within minimal web browsers, the MAPD system implements media object sending through the alternate HTTP channel using the HTML<FILE>element. Once the end user (originator) clicks to send the media object, it is converted to a multi-part mime format for sending to the MAPD system central servers.

5

The Aprepare and post@ tool also supports a batch interface, allowing a plurality of media objects to be Abatched@ and submitted simultaneously. Most users who are using media objects work with several media objects at the same time versus one media object at a time. Therefore, it is desirable to submit 5, 10 or 25 media  
10 objects for processing and distribution at one time for efficiency without having to repeat steps for each of the media objects. An example is a professional photographer who may need to submit several media objects at the same time to several destination web sites. Quickly clicking and dragging a plurality of media objects for submission with the MAPD system is as easy and efficient as submitting  
15 one media object.

The description of the present invention thus far has discussed that a media object can be obtained from a single source or from multiple origination sources and that a media object can be transmitted to a single destination and to multiple  
20 destinations. The point-to-multi-point distribution is a key advantage of the present invention. This multi-point distribution may be accomplished using distribution lists stored at MAPD system central servers. Distribution lists stored within the MAPD database provide a way for MAPD system customers to specify which of their affiliate web sites get mirrored copies of images submitted through the mirror service  
25 distributed directly to them. In technical terms, a distribution list is a named entity that binds a group of destination web sites with a customer via the mirror service. When a media object arrives from a customer on the mirror service, the MAPD system uses the customer's named distribution list to establish which web site servers (i.e., customer affiliate locations) receive copies of the media object. Figure 12  
30 shows this point-to-multi-point distribution relationship as it is managed by the service link and the distribution list, as will be described herein below.

Each entity in a distribution list has an associated client profile that identifies the remote servers for the destination web sites, the delivery method and any number of processing filters to apply to the media object before sending. Filters are used to control the attributes of media object content delivered to clients, which are tied to the customer profiles. Filters can also be employed to increase functionality within the MAPD system architecture. The attributes may include dimensions, quality and type of media object delivered (i.e., slide show, video) etc. Filters are applied to inbound media objects or outbound media objects or both and are used for both the MAPD system host and mirror service.

More particularly, filters may be associated with both services and clients. Service filters are applied as the media object is received. For mirror services, the service filter is applied as the media object arrives, before it is stored. As the mirror service distributes the media object to clients, the appropriate filter for each client is applied before the media object is sent. For example, a particular mirror service may convert all images to 320 x 200 jpeg before storing them, and then convert those to the specific requirements of each client on its distribution list prior to transporting the images. For the hosting service, the service filter is applied as the media object is received, and then the appropriate client filter is applied to the result before the media object is stored. Clients and services can share filters. If no filters associated with a given service or client handle a particular file type, then media objects with that file type are not converted for that service or client.

Depending on the particular service, image processing may be performed primarily at the client using the Aprepare and post@ tool, primarily at a MAPD system central server, or may be performed at both, some at the client and some at the MAPD system central server. In the case of the host service, for example, image requirements may be specified within a particular instance of the Aprepare and post@ tool as it is integrated into the web page of a particular customer. Processing the image within the Aprepare and post@ tool avoids unnecessary data transfer. In the case of the mirror service, for example, more than one processed image may be

produced from the original image submission. Image processing may therefore be performed primarily at the central server. Nevertheless, basic sizing and resampling may be performed at the client, avoiding the circumstance in which a novice user attempts to upload a huge image file, causing their network connection to "choke."

Although media processing will often involve sizing and formatting of images, any of various kinds of media processing may be performed by the MAPD system media processing engine, for example enhancements and effects, text and graphic layering, image stitching, streaming video encoding, producing zoomable images, cropping, rotating, etc.

For instance, in one embodiment, resizing and format conversion of still images may be performed on either the client or central server. In another embodiment video image encoding may be performed on either the client or central server. In still another embodiment, still images are resized by determining on the central server a maximum still image size for all destination web sites such that the still images are resized no larger than the maximum size on the central server. In this case, resizing of the image may also be performed on the client.

Furthermore, although the MAPD systems have been described as having a central server, any suitable server architecture may be used to support MAPD system services. One type of architecture that is complementary to MAPD system services is a distributed server architecture and global content distribution service offered by Akamai Technologies, Inc. of Cambridge, MA under the name Freeflow™. The Freeflow content distribution method allows content providers to ensure rapid access to their sites without needing to maintain burdensome and expensive content distribution infrastructure, using a global network of specialized servers and software that controls how content is distributed throughout the network. Rapid access is achieved by moving bandwidth-intensive content closer to the user. Web site performance is optimized by migrating content according to its popularity while taking into account changing network conditions and fluctuations in traffic. The

MAPD system may optionally pass information to this distributed server environment or others, as needed, in order to optimize delivery of the media content the MAPD system creates.

5 Referring to Figure 6 therefore, a block diagram of the MAPD system network imaging architecture is shown. A MAPD system Media Acquisition and Distribution layer (MAPD system central server) provides for media object processing in accordance with customer profiles, and for multi-point distribution as described. Above the MAPD system Media Acquisition and Distribution layer may  
10 be various service layers including zoomable images, streaming video encoding, image stitching, slide shows, text and graphic layering, enhancement and effects, sizing and formatting. The architecture is easily extended by added new services as needed. Below the MAPD system Media Acquisition and Distribution layer is the optional distributed server infrastructure, which may be a global hosting  
15 infrastructure such as that of Akamai or any other advantageous server infrastructure partner.

Recognizing that any of various server infrastructures may be used, the MAPD system central hardware architecture in accordance with an exemplary  
20 embodiment of the invention will be described. Referring to Figure 7, an example of how the MAPD system mirroring system hardware could be partitioned is detailed. A cluster organization is followed that uses three clusters, an inbound cluster, a file server cluster and an outbound cluster. The file server cluster is attached to a MAPD system database, or repository. Web submissions from the MAPD system Aprepare  
25 and post@ tool are received by the inbound cluster. Within the inbound cluster, the MAPD system repository is consulted in order to form a distribution request, which is sent to a distribution queue at the outbound cluster through a remote interface. Within the outbound cluster, distribution requests are polled and processed by picking up items from the distribution queue and building a distribution list based on  
30 the corresponding customer's profile. For each destination in the distribution list, a distribution server within the outbound cluster makes a socket connection to the



second location and delivers the media object.

Because of the ability to have a media object sent to multiple destinations, the number of outbound transactions is potentially far greater than the number of inbound transactions. To facilitate the transfer of media objects, inbound media processing is separated from outbound media processing. This separation is accomplished by the MAPD system distribution queue. In an exemplary embodiment, the MAPD system distribution queue is a runtime Remote Method Invocation (RMI) object shared between multiple MAPD systems and outbound distribution processors. Referring more particularly to Figure 8, when a submission arrives for the mirror service, it is received by an inbound mirror processor. The inbound mirror processor stores the submission within the MAPD system repository and adds a distribution object to the distribution queue. The outbound media distributor constantly polls the distribution queue for available items and when one is available, removes it from the queue and carries out the distribution. A single inbound submission to the mirror service typically results in multiple distributions to customer affiliate locations, since the purpose of the mirror service is to allow MAPD system customers to distribute media to that customer's affiliates using a distribution list. Once the outbound media distributor pulls an item off the distribution queue, it is responsible to build a distribution list of all intended recipients and carry out the transfer of media.

A ClientHoldingQueue object may be provided as a holding area for transactions destined for a customer which is unreachable. These transactions are queued as distribution objects until the customer becomes reachable and they can be sent. A ClientHoldingQueue contains a queue of distribution objects similar to the primary queue. It has its own thread to process that queue and it contains the ability to ping its customer as a way of knowing when the customer comes back on line. ClientHoldingQueues are created whenever a normal transmission fails and they go out of existence as soon as they are able to deliver all of their queued objects.

The MAPD system may be realized in two tiers (traditional client/server), three tiers, or, more generally, N tiers. A three-tier implementation in accordance with an exemplary embodiment of the invention is illustrated in Figure 9. The three-tier partitioning includes a client tier, an application tier and a database tier. 5 Beside tier boundaries, also identified are IP (internet protocol) boundaries. Communication across IP boundaries occurs, for example, through the Internet using the Internet Protocol (IP). A vertical IP boundary separates client (sources) from consumers (destinations). A horizontal IP boundary separates (browser-based) client from servers.

10 In operation, submission tools (Aprepare and post@) are used to submit media to a central server where the media objects are processed as necessary, stored, and distributed, either by hosting or mirroring. In the case of mirroring, the outbound servers send the media object to a mirrored client repository, causing the media 15 object to be stored within a mirrored database. The media object is accessed from the mirrored client repository using distribution tools and viewers, in particular web browsers. Such access may be accomplished, for example, through Active Server Pages (ASP) or Cold Fusion (CF) for server-side page generation. In the case of hosting, the media object is accessed directly from the MAPD system central servers, 20 using the same or similar techniques, for example.

Referring to Figure 10, the principal MAPD system database system entities (tables) and their relationships are shown in accordance with an exemplary embodiment. Appendix A details the associated database tables. The Account table 25 contains primary account information for each MAPD system service customer. There is only one account record for each MAPD system customer. The ClientProfile table contains profile information used to control customer access to MAPD system services. A MAPD system customer will typically have a single client profile, but may in some instances have more than one customer profile, e.g., 30 if a customer has multiple business units, one or more of which subscribes to MAPD system services. The user table defines users with access rights to account

information for a given customer.

The Distribution Link table is used to identify a distribution list associated with the mirror service via a ServiceLink record. The ServiceLink.Distribution-  
Listname and the ServiceLink.ServiceLinkID are used to identify all the  
DistributionLink records that are targeted for a media distribution to a second  
location. Each DistributionLink record identifies a profile  
(DistributionLink.ProfileID) which identifies the second location for the distribution  
as well as media distribution characteristics (e.g., filter, applications, etc.).

The Server table identifies various MAPD systems used to process inbound  
traffic, outbound traffic and media storage. The ErrorLog table records errors in  
inbound and outbound traffic processing.

The StorageVolume table contains descriptions of MAPD system central  
server volumes used for media storage. A given service uses a StorageVolume  
record to identify the server and volume where media will be stored. The physical  
and virtual paths used to identify the folder location for media items are identified  
via a StorageLink record in the StorageLink table. The StorageLink table contains  
physical and virtual folder locations within a given StorageVolume. It is used for  
identifying the storage location of media items within the MAPD system central  
server.

The MediaMaster table contains one entry for each unique media element  
stored in the MAPD system repository. The MediaType table identifies classes of  
media associated with MAPD system services. The Industry table describes  
industries associated with MAPD system customers. It may be based on the NAICS  
industry codes standard.

The Service table describes all available MAPD system services. The  
ServiceLink table contains associative records which identify customer-specific

service characteristics or properties associated with a given service. The Filter table contains filter records. Each filter record defines activities or constraints applied to media. The FilterLink table contains associative records which identify filters associated with a given customer.

Further details concerning MAPD system filters and their implementation is found in Appendix B.

As illustrated in Figure 11, in general terms, ServiceLinks link an Account to one or more services and ultimately, through StorageLink and StorageVolume entities, to a physical media storage location.

In the case of the mirror service, DistributionLink and ClientProfile entities control the distribution process as illustrated in Figure 12. When a submission arrives for the mirror service, it is stored within the MAPD system central repository and mirrored to a customer (second location) or customer affiliate locations. The second location and the affiliate locations use MAPD system software, particularly a MAPD system ClientReceiver, to process and store media objects and data. When the media object submission arrives the userID and password are used to lookup the associated Account (1) record. Once the account has been identified, the AccountId and service name (in this instance "MIRROR") are used to find the ServiceLink (2) record associated with the account for the mirror service. The ServiceLink record identifies the distribution list to mirror the submission to. Given a ServiceLinkId and a DistributionName, the DistributionLink (3) table is used to identify the target ClientProfile (4) records used to mirror the submission. The ClientProfile (4) record contains the IP address and port of the mirror site (second location).

The MAPD system communicates with clients to send mirrored media objects through TCP/IP sockets. A MAPD system ClientReceiver is a software agent that sits at the customer site and waits (e.g., on a pre-defined port) for connections from the MAPD system. In an exemplary embodiment, the port is

stored with the customer profile in the MAPD system repository and fetched by the media distributor to make the customer connection. Other delivery methods may be used instead of sockets, e.g., HTTP file send, FTP push, e-mail etc.

5           In order to effectively use the media objects, to match media objects with customer's databases, customers need to be able to automatically integrate incoming media objects (received from MAPD system distribution servers) into their existing database structures. In an exemplary embodiment, a method shown in Figure 13 is called when a new media object arrives at the customer site (remote destination web  
10   site) via the MAPD system ClientReceiver. The ClientReceiver automatically takes the media object that has been sent from MAPD system central and stores it to disk (i.e., line "String filename," in Figure 13). The storage location is specified in a properties file at the customer's receiving site. The ClientReceiver also passes the information about the media object (unique ID number, sequence number,  
15   description fields, etc.) to a function which can be modified at the customer's receiving location as well (i.e., lines "String mediaGroupID", "String media ExtID", "int seqNum", "int industry Code", "String desc1", "String desc2", and "String desc3", in Figure 13). The MAPD system provides a function that can be modified to provide the customer's own database with the information the MAPD system passed  
20   to the function. Once the new media object has been integrated into the customer's database, it can be immediately used in server-side page generation as a page is requested by a web site visitor.

25           The function typically stores the media object information in a proprietary database (the MAPD system customer's database). The body of the function is commented out so the customer or the customer's affiliate locations can fill it out with specific instructions (source code to the Java class that contains this function is provided by the MAPD system). The function parameters reflect what was provided during the media object submission using the image submission tool.

30           MAPD system customers who subscribe to the "mirror" service specify their

own servers or affiliate server locations who are approved to receive mirrored copies of the media objects or information about the media objects, such as IMG SRC URL, from the MAPD system. To specify which affiliates receive mirrored information, a distribution list is set up and a small profile is entered for each affiliate in the database. The initial steps for setting up a customer for the mirror service are:

1. A registration form is completed that contains standard entries such as an ID, password, full name, address, phone, e-mail, fax, etc. MAPD system central server uses this information to establish a service record(s) for the customer account.

2. Distribution list forms are completed for each approved affiliate or customer server and appropriate information such as IP address to send images to, transformations to be performed on media objects etc. MAPD system central server uses this information to establish a profile for each affiliate.

The profile contains the preferred delivery method (ClientReceiver, e-mail or FTP for the mirror service.) For delivery by the ClientReceiver, the entry contains the IP address and Port for the ClientReceiver.

The MAPD system ClientReceiver is provided to the customer and, in an exemplary embodiment, is a Java application or process that runs on any platform supporting the generic JDK 1.1 or later versions. The ClientReceiver sits on one of the customer's remote web servers or one or more customer's affiliate locations per the customer's designation. When media objects are received by MAPD systems from the Aprepare and post@ media submission tools, they are processed according to the customer's specifications as described earlier and forwarded to any approved affiliate locations by making a socket connection to ClientReceivers installed on the customer's behalf.

In the case where the affiliate locations intended for mirrored delivery cannot install the ClientReceiver or they prefer delivery by a different method, the media

object submissions can alternatively be forwarded via other methods such as FTP or by e-mail. The MAPD system is set up to specify delivery instructions by any number of methods including but not limited to ClientReceiver, FTP or e-mail on an affiliate-by-affiliate basis. For example, if Customer #1 wants media objects to be sent to 3 affiliates in a distribution list called "PrimaryAffiliates" (and there can be more than one distribution list), tables at MAPD system central may be set up for delivery by ClientReceiver to the first affiliate, FTP to the second and e-mail to the third. The MAPD system can be configured to have unique and varied distribution lists per the customer's instructions.

The following Appendices C and D describe in greater detail the program architecture for the Image Container (media object identifier) and COM (media sender) components used in an exemplary embodiment of the invention. Appendix E is a general description of the ClientReceiver class used in an exemplary embodiment of the invention.

## APPENDIX A

### **Account Table**

#### **Description:**

This table contains accounting information for each MAPD service partner. There is only one account record for each MAPD partner.

Field Name	Data Type	Length	Description
AccountID	varchar2	20	Unique Account ID
AccountName	varchar2	50	Textual name of account
Password	varchar2	10	Used for log in
Address1	varchar2	80	
Address2	varchar2	80	
City	varchar2	50	
State	varchar2	25	
Zip	varchar2	10	
Country	varchar2	20	
PrimaryContract	varchar2	50	
Phone	varchar2	20	
Email	varchar2	50	
Website	varchar2	80	
Fax	varchar2	20	
Industry	Number	5	industry associated with this account
UserLifeSpan	Number	11	Users of this account live this long by default

### **ClientProfile Table**

#### **Description:**

This table contains profile information used to control client access to MAPD services. A MAPD partner may have more than one client profile (though there is only one typically). This would be the case if a partner has multiple business units, one or more of which subscribes to MAPD services.

Field Name	Data Type	Length	Description
ProfileID	Number	11	Auto-incremented Unique ID
ClientAccount	varchar2	20	AccountName link to Account Table (e.g., Pacific Union)
ProfileName	varchar2	20	Textual name for this profile (e.g., PacUnion1)
ClientIndustry	Number	5	Industry type for this client. Media that come in from this client and are (by default) associated with this industry.
ReceiverHost	varchar2	80	Client media receiver URL
ReceiverPort	Number	5	Port to receive on
LocalPort	varchar2	5	Use this port for outbound traffic -- currently not in use (defaults to port 0)
DeliveryMethod	varchar2	80	Class file of primary delivery method
AltDeliveryMethod	varchar2	80	Class file of alternate delivery method
DeliveryEmail	varchar2	50	Email address for DeliveryMethod (email)
EmailFormatTemplate	varchar2	2048	Text template for mirroring images via email
AutoLogID	varchar2	50	server-to-server connection id
AutoLogPassword	varchar2	10	server-to-server connection password
DefAccessRights	Number	4	default access rights for this profile

### **DistributionLink**

#### **Description**



## APPENDIX A (Cont'd)

This table is used to identify a distribution list associated with the MIRROR service via a ServiceLink record. The ServiceLink.DistributionListname and the ServiceLink.ServiceLinkID are used to identify all the DistributionLink records that are targeted for a media distribution. Each DistributionLink record identifies a profile (DistributionLink.ProfileID) which identifies the target server for the distribution as well as media distribution characteristics (e.g., filter application, etc.)

Field Name	Data Type	Length	Description
DistributionID	Number	6	Auto-incremented Unique ID
ServiceLinkID	Number	4	Groups distribution items by ServiceLinkID
ProfileID	Number	11	Identifies the target ClientProfile record
DistributionName	varchar2	20	Distribution List name – groups distributions by name for a given account and service (via a ServiceLink record)

### *StorageLink*

#### Description:

This table contains descriptions of MAPD Central server volumes used for media storage. A given service uses a *StorageLink* record to identify the server and volume where media will be stored. The physical and virtual paths used to identify the folder location for media items are also identified.

Field Name	Data Type	Length	Description
VolumeLinkID	Number	11	Auto-incremented primary key
ServerName	varchar2	30	Server name (e.g., DELL)
VolumeName	varchar2	30	Name of Volume within MAPD (e.g., DriveC -- \\DELL\DriveC)
IPAddress	varchar2	80	IP address of server associated with this volume
PhysicalDir	varchar2	255	Physical location within volume (e.g., \inetpub\wwwroot\mywebserver)
VirtualDir	varchar2	255	Virtual directory (e.g., \PWIS\images\hostimages)
Status	Number	2	Status: 1 = active, 0=inactive

### *MediaMaster Table*

#### Description:

This table contains one entry for each unique media element stored in the MAPD repository.

Field Name	Data Type	Length	Description
MediaID	Number	11	Auto-incremented Unique key
MediaGroupID	varchar2	150	Industry-specific ID (e.g., MLS number)
MediaExtendedID	varchar2	100	Media id qualifier such as zipcode
MediaSequenceNum	Number	4	Identifies media item within a set (e.g., MediaGroupID+ExtendedID+SequenceNum)
MediaType	Number	3	stored media format (1 = jpg image, 2 = fpx image, 3 = gif, 4 = panorama)
OrigName	varchar2	80	Original name of media item at point of submission (i.e., the physical file that was sent – even if a temp file) Does not include path.

## APPENDIX A (Cont'd)

MediaName	varchar2	80	Name of item stored on MAPD server. Does not include path.
MediaLocation	Number	4	foreign key to StorageLink. IMPORTANT NOTE: Do not modify the locations inside a StorageLink record; since old media items will point to an invalid location. If new storage locations need to be assigned to a service, then create a new storageLink record and use that.
ServiceID	varchar2	20	Service requested which resulted in this item being created
IndustryCode	Number	5	Item is associated with this industry (NAICS code) – 0 means unspecified
Description1	varchar2	255	arbitrary values (e.g., room name for a real estate image)
Description2	varchar2	255	arbitrary values
Description3	varchar2	255	arbitrary values
DateCreated	Date/Time		date media item created
ClientID	varchar2	20	ID of partner who initiated media upload
SubmittorID	varchar2	50	ID of person who submitted media item
SubmittorPassword	varchar2	10	Password of person who submitted media item
AccessRights	Number	4	default 1 = Public (anyone subscribing to Mirroring has access), 0=submitter and affiliates only
HasThumb	Number	1	1 if there is a thumbnail associated with this item
ImageWidth	Number	6	Width of media image
ImageHeight	Number	6	Height of media image

### **Service Table**

Description:

This table describes all available MAPD services.

Field Name	Data Type	Length	Description
ServiceID	varchar2	20	Unique ID identifying the service
ServiceType	Number	4	Identifies service type for this industry group
DefaultServerID	varchar2	20	default MAPD server ID for this service
DefaultPort	varchar2	5	default MAPD port for service
DefaultStorageFormat	Number	5	default stored format (e.g., FPX)
DefaultFilter	Number	5	default filter for client delivery

## APPENDIX A (Cont'd)

### ***Filter Table***

#### **Description:**

This table contains filter records. Each filter record defines actives or constraints applied to media.

Field Name	Data Type	Length	Description
FilterID	Number	5	Media filter ID
FilterClassName	varchar2	80	Java class name of filter.
MediaFileType	varchar2	20	Type (file extension) of media to which this filter should be applied.
Convert	Number		1 if the media is to be converted to another type (file extension.) 0 otherwise.
DestinationFileType	varchar2	50	Output type if above is yes.
DestinationQuality	Number	11	Output quality (currently only applies to jpeg files.)
Resize	Number		1 if the media is to be resized. 0 otherwise.
AllowExpand	Number		1 if the media can be increased in size. 0 Otherwise
DestinationWidth	Number		Output width of media.
DestinationHeight	Number		Output height of media.
Template	varchar2	255	Fully-qualified path of conversion template (if used)
TemplateClass	varchar2	80	Class which implements positioning logic (obsolete?)

### ***Industry Table***

#### **Description:**

This table describes industries associated with MAPD partners. It is based on the NAICS industry codes standard.

Field Name	Data Type	Length	Description
IndustryID	Number		Auto-incremented. Any client may be associated with multiple industries
MajorIndustryCode	Number		Major Industry code—from US Dept of Labor (example 65 = Real Estate)
MinorIndustryCode	Number		Minor code (eg. 653 == Real Estate Agents and Managers)
IndustryName	varchar2	50	Name or type of industry (e.g., Auto)

### ***ServerControl Table***

#### **Description:**

This table identifies the various MAPD servers used to process Inbound traffic, Outbound traffic and media storage.

Field Name	Data Type	Length	Description
ServerControlID	Number	4	Unique id
ServerType	varchar2	16	type of server
IPAddress	varchar2	80	IP address of this server
ControlPort	varchar2	50	server port address
Status	Number	2	status: 1= active, 0 =

## APPENDIX A (Cont'd)

			inactive
--	--	--	----------

### ***ServiceLink Table***

#### **Description:**

This table contains associative records which identify client-specific service characteristics or properties associated with a given service.

Field Name	Data Type	Length	Description
ID	Number	4	Unique ID for this association
AccountID	varchar2	20	account id associated with this linklink to ClientProfile table
ServiceID	varchar2	20	link to Service Table
ProfileID	Number		link to ClientProfile table – contains the default profile associated with this account
IndustryCode	Number		US Department of Labor Major industry code (NAICS)
Priority	Number	3	default = 1 (highest). this is used to decide how/when to forward media associated with this service to the linked client
OriginatorSend	Yes/No		default = false, if true, media for this service sent by this originator and its affiliates is distributed only to the originator. Answers the question: Whom do you want to allow to receive this media item?
ForeignSend	Yes/No		Default = true, if false, this client only wants media for this service which originated from this client and its affiliates. Answers the question: Whose media do you want to receive?
DistributionList	varchar2	2000	List of semi-column separated named distribution lists. Each item organizes a list of destinations, with each destination being associated with a client profile containing a delivery method, IP addresses, etc.
SubmitSelList	varchar2	2000	Image well default selection list for this client's service
StorageLinkID	Number		Link to storage locator record
StorageGenerator	varchar2	50	class name of storage constructor class
MaxMediaPerUser	Number	10	maximum submissions for a single user of this service
SecurityClass	varchar2	50	class name of security class. Run on server at submission reception time.
MediaLifeSpan	Number		Lifespan of media received on this service

### ***FilterLink Table***

#### **Description:**

This table contains associative records which identify filters associated with a given client.

Field Name	Data Type	Length	Description
FilterLinkID	Number		Auto-incremented Unique ID
ServiceLinkID	Number	4	Apply filter to media inbound to this service
ClientProfileID	Number		The filter below is associated with this client
FilterID	varchar2	64	comma-delimited list of filterids from filter table

## APPENDIX A (Cont'd)

### **ErrorLog Table**

Description:

This table records errors in Inbound and Outbound traffic processing.

Field Name	Data Type	Length	Description
ErrorLogID	Number	11	Auto-incremented Unique ID
TimeOfOccurrence	Date		Date & Time of occurrence
Media	Number	11	ID of media item processed
Host	varchar2	50	Host ID of inbound/outbound transaction
Port	Number	5	Port error occurred on
ClassName	varchar2	50	Java classname where error occurred
FunctionName	varchar2	50	Java function within class
Severity	varchar2	50	severity code
Reason	varchar2	128	reason for error
Response	varchar2	128	action taken in response to error
Context	varchar2	255	general description
Exception	varchar2	255	java exception

### **ServerControl Table**

Description:

This table contains the location (IP Address) and execution status MAPD server processes. It is used to register servers so they may receive external communication commands (see *External Commands* for details.)

Field Name	Data Type	Length	Description
ServerControlID	AutoNumber		Unique ID
ServerType	Number		Apply filter to media inbound to this service
IPAddress	Number		The filter below is associated with this client
ControlPort	Number		Link to filter table
Status	Number		0 = not running, 1 if currently running

### **User\_r Table**

Description:

This table defines users with access rights to account information for a given partner. Note that the names *User\_r* and *Privileges\_r* are named as such because Oracle reserves the names User and Privileges within its namespace.

Field Name	Data Type	Length	Description
UserID	AutoNumber		Unique ID
FirstName	varchar2	20	e.g., Fred
MiddleInit	varchar2	3	
LastName	varchar2	20	
User_r	varchar2	50	e.g., freds – up to 10 alpha numeric
Password	varchar2	10	up to 10 alphanumeric
AccountID	varchar2	20	link to account table
OfficeID	varchar2	20	
Phone	varchar2	20	contact phone number
Email	varchar2	50	email address

## APPENDIX A (Cont'd)

Privileges_r	Number	5	Administration access rights
SupportLevel	Number	5	
CreateDate	Date		date user added to system
MaxSubmissionsAllowed	Number	50	This user can only have 50 active media items. if -1, then use default from servicelink
LastAccessDate	Date		Last time logged on
SendEmailUpdates	Number	1	marketing stuff
ShareContactInfo	Number	1	marketing stuff

### ***DistributionLink Table***

Description:

This table defines members of a distribution list. A distribution list is a named entity (DistributionName). A list is a collection of DistributionLink all with the same DistributionName and same.

Field Name	Data Type	Length	Description
DistributionID	Number	6	Unique ID
ServiceLinkID	Number	4	Groups distribution items by ServiceLink
ProfileID	Number		Identifies the target client profile
DistributionName	varchar2	20	Distribution List name – groups distributions by name for a given account and service (via ServiceLink)

### ***Maintenance Table***

Description:

This table is used to schedule database object and media retirement activities.

Field Name	Data Type	Length	Description
RetireNextRun	Date		Date/time of next retire run
RetireIntervalDays	Number		Number of days between retire runs
RetireLogFileName	Number		Next log file number to write retire log to
TempDate	Date		temporary date/time storage for runs

### ***Transaction Table***

Description:

The 'Transaction' database table contains one entry for each transaction that is in progress or has taken place.

Field Name	Data Type	Length	Description
TransactionID	Number		Unique identifier generated by database
State	Number	5	Current transaction state – UNKNOWN, RECEIVED, QUEUED, HELD, SEND, FAILED
MediaID	Number		Identifier of media item being received or sent
Bytes	Number		Number of bytes received or sent in this transaction
ServiceLinkID	Number	4	ServiceLink under which this media was received
ClientProfileID	Number		Destination (outgoing transactions only)
TimeCreated	Date		Database time stamp when this transaction was created
TimeCompleted	Date		Database time stamp when this transaction was

## APPENDIX B

### Database considerations for Filters

Each service and each client has a set of 0 or more filters associated with it. Filters are represented as entries in a 'Filter' Table. Filters are associated with services or clients by entries in a 'FilterLink' table. Each FilterLink entry maps one filter to one clientservice and/or one client. Note that clients services and clients can share filters.

Filter table entries specify the name of a filter (a java class, see Extensibility below) and other attributes required by the filter such as output dimensions for an image filter. They also indicate the file type (extension) to which they are to be applied. This is either a specific file extension, or 'ALL.' ALL means the filter is the default for any media with a file type which the filter handles, (see *handlesType* below).

For example, a filter class called 'soundFilter' handles .wav, and .riff extensions. An entry in the Filter Table defines filter 7 as class soundFilter and as applying to all .wav files. Filter 8 is also a soundFilter and defined to apply to 'ALL' files. Entries in the FilterLink Table associate both filter 8 and 9 with Client X. A wav file is destined for Client X. The system looks at the filter set for Client X, sees filter 8 which is a soundFilter, (handles wav files as well as others), and sees that filter 8 has wav listed as the type to which it is to be applied. Filter 8 will take precedence over filter 9 which is also a soundFilter, but is configured for 'ALL.' A specific type match will always take precedence over 'ALL.' Any riff files bound for Client X will be handled by filter 9.

If no filters associated with a given service or client handle a particular file type, then media with that file type are not converted for that service or client.

### Filter Extensibility

Filters are implemented as java classes. All filter classes provide a common interface, which includes the following functions:

*Constructor* – takes a database filter table entry id as a parameter and initializes an instance of this filter with the attributes specified in that entry.

*handlesType* – given a file extension this returns true if the filter handles media with that extension  
*convert* – this performs the conversion.

*Compare* – returns a comparison value between two filters. This is used to sort media during distribution for efficiency. By ordering destination clients for a particular outbound media according to the filters associated with those clients, identical sets of filters will be adjacent in the order. This means that the media need only be converted once per set of identical filters.

Filters are loaded dynamically, which means new filters can be developed, shipped, and installed while the system is running.

### Example

Take the case where client X wants to receive all images as jpg files scaled to 320x240 with a quality of 90. To do this, we create the following filter in the filter table:

FilterClassName = ImageFilter

MediaFileType = ALL

DestinationFileType = jpg

DestinationWidth = 320

DestinationHeight = 240

DestinationQuality = 90

Next, we create an entry in the FilterLink table as follows:

ClientProfileID = client X's Client Profile ID

FilterID = ID of filter created above

Note that the ImageFilter is implemented in ImageFilter.class. It handles jpg files among others. In the example above, it will be used to convert all file types that it handles to jpg files with the specified dimensions and quality.

**BEST AVAILABLE COPY**

**APPENDIX C**

*PWTImgCont.ocx -- Activex Image Container Component*

Interface Name	Type	Definition	Signature
ScaleImage	function	Scales an image in place or to a temporary file	ScaleImage( destWidth As Integer, destHeight As Integer, destQuality As Integer, '0-100 generateOutputFilename As Boolean ' create tempfile ) As String
DelTempFile	sub	Deletes temporary file created with ScaleImage	DelTempfile()
fileName	String property	Name of file shown in image well	fileName as String
imageName	String property	String value from image caption box	imageName as String



APPENDIX D

PWISFileSend.dll

- COM component for sending media to server

Interface Name	Type	Definition	Signature
SubmitMediaRequest	sub	Transfers image	SubmitMediaRequest( UserID As String, 'partner UID Password As String, 'partner password ServiceType As String, ' "HOST" or "MIRROR" IndustryCode As Integer, 'e.g., 65=real estate MediaType As Integer, '1=image 2=video 3=sound OpCode As Integer, '1=Add, 2=Update, 3=Delete IPAddr As String, 'Destination IP address filename As String, 'File to send MediaGroupID As String, 'Used to build unique key MediaExtendedID As String, '"" MediaSequenceNum As Integer, '"" Desc1 As String, '255 chars Desc2 As String, '255 chars Desc3 As String) '255 chars
retCode	read-only integer property	Return code from SubmitMediaRequest	retCode as Integer
Scaled	integer property	Indicates whether image was pre-scaled before being sent	Scaled as Integer
ServerRetString	String property	Return value from SubmitMediaRequest. If call made on HOST service, this string contains the IMG SRC url	ServerRetString as String

Usage Example (VB Script)

```

tempFileName = DragImage1.ScaleImage(320, 240, 89, 1) ' scale the image object 'DragImage1'
result = UplHandler.SubmitMediaRequest(                ' transmit to mad central
    UserID,
    Password,
    ServiceType,
    0,
    1,
    1,
    ipAddress,
    tempFileName,
    mlsNum.Value,
    zipcode,
    imageCount,
    title,
    desc2,
    desc3)
DragImage3.DeleteTempFile                             'delete the temp file

```

**Client Receiver**

Name	Type	Description	Location	Constraints
ClientMediaReceiver.java	Java class	Client Media Handler. Handles incoming MAD media distributions. Media arrive as a binary stream with an encoded descriptive property set. Invokes an instance of the ClientDBBinder to enable data integration at client site (see below).	Java Source: MADS\ClientReceiver  Classfile: MADS\ClientReceiver/Classes	JDK 1.1 compatible. Runs under any operating environment support that version of the JDK (e.g., NT, Windows 9x, Solaris, Mac, etc.)
ClientDBBinder.java	Java class	This is a reference implementation (with source code) of a	Java Source: MADS\ClientReceiver	We cannot integrate directly into the client's
		component which is used to integrate incoming media into the client's database. The choice of a Java Bean or COM component is made by the client at installation time.	Classfile: MADS\ClientReceiver/Classes	database unless we understand it's structure. Since in many cases we won't understand it, it's best to provide a reference implementation instructing how to integrate the media properties into a database table structure.
ClientMediaReceiver.props	Client Receiver Properties File	This is a properties file installed at the client receiver site. It defines operating parameters for client media reception such as default storage locations, etc.	MADS\ClientReceiver	This file should be extended by the client to identify appropriate database entries (DSN, drivers, default storage tables, etc.).
startclientreceiver.bat	batch file	starts the ClientReceiver service	MADS\ClientReceiver	Specifies the name of the controlling properties file on the command line.